

































PE-Rohre und Zubehör Sortiment

Geberit Vertriebs GmbH & Co KG
 Geberitstr. 1, 3140 Pottenbrunn/St.Pölten
 Tel.: 02742/401-0, Fax: 02742/401-50
 www.geberit.at


















Art.-Nr.	Dimension	Anzahl	Art.-Nr.	Dimension	Anzahl	Art.-Nr.	Dimension	Anzahl
 PE-Rohre, getempert, in Stangen zu 5 m			 Bogen 45°			 Bogen 90° mit großem Radius		
379.000	32		360.045	40		370.055	200	
360.000	40		361.045	50		371.055	250	
361.000	50		363.045	56		372.055	315	
363.000	56		364.045	63				
364.000	63		365.045	75				
365.000	75		366.045	90		 Bogen 90°		
366.000	90		367.045	110				
367.000	110		368.045	125				
368.000	125		369.045	160				
369.000	160							
370.000	200							
371.000	250							
372.000	315		 Bogen 45° mit langem Schenkel			379.055	32	
			367.046	110		360.055	40	
 PE-Rohre verstärkt, für erhöhten Unterdruck bei Pluvia Dachentwässerungssystem			 Bogen 15° mit großem Radius			361.055	50	
370.050	200		370.015	200		363.055	56	
371.050	250		371.015	250		364.055	63	
372.050	315		372.015	315		365.055	75	
						366.055	90	
						367.055	110	
						368.055	125	
						369.055	160	
 Tragschalen, in Stangen zu 3 m			 Bogen 90° mit engem Radius			 Bogen 90° mit engem Radius		
360.850	40					366.876	90	
361.850	50		 Bogen 30° mit großem Radius			367.876	110	
363.850	56		370.030	200		 Anschlusswinkel 88 1/2°		
364.850	63		371.030	250				
365.850	75		372.030	315				
366.850	90		 Bogen 45° mit großem Radius					
367.850	110		370.045	200				
368.850	125		371.045	250				
369.850	160		372.045	315				
370.850	200							
371.850	250							
372.850	315							

Art.-Nr.	Dimension	Anzahl	Art.-Nr.	Dimension	Anzahl	Art.-Nr.	Dimension	Anzahl
	Putzstück 90° mit Verschlusskappe			PE-Abzweiger 45°, für waagrechten Einbau			PE-Abzweiger 88 1/2°, nur für Falleleitungen	
364.451	63		367.135	110/110		379.158	32/32	
365.451	75		368.120	125/63		360.158	40/32	
366.451	90		368.125	125/75		360.159	40/40	
367.451	110		368.135	125/110		361.159	50/40	
368.451	125		368.139	125/125		361.162	50/50	
369.451	160		369.125	160/75		363.162	56/50	
			369.135	160/110		363.165	56/56	
			369.139	160/125		364.162	63/50	
			369.145	160/160		364.165	63/56	
	Putzstück mit ovalem Verschlussdeckel		370.135	200/110		364.170	63/63	
367.454	110		370.139	200/125		365.162	75/50	
368.454	125		370.145	200/160		365.165	75/56	
369.454	160		370.146	200/200		365.170	75/63	
370.454	200		371.135	250/110		365.175	75/75	
371.454	250		371.139	250/125		366.180	90/90	
372.454	315		371.145	250/160		367.159	110/40	
			371.146	250/200		367.162	110/50	
			371.147	250/250		367.165	110/56	
			372.135	315/110		367.170	110/63	
			372.139	315/125		367.175	110/75	
			372.145	315/160		367.180	110/90	
			372.146	315/200		367.185	110/110	
			372.147	315/250		368.162	125/50	
			372.148	315/315		368.165	125/56	
						368.170	125/63	
	PE-Abzweiger 45°, für waagrechten Einbau					368.175	125/75	
379.108	32/32					368.185	125/110	
360.108	40/32					368.189	125/125	
360.109	40/40					369.175	160/75	
361.109	50/40					369.185	160/110	
361.112	50/50					369.189	160/125	
363.112	56/50					369.195	160/160	
363.115	56/56					370.185	200/110	
364.112	63/50					370.189	200/125	
364.115	63/56					370.195	200/160	
364.120	63/63					370.196	200/200	
365.112	75/50					371.185	250/110	
365.115	75/56					371.189	250/125	
365.120	75/63					371.195	250/160	
365.125	75/75					371.196	250/200	
366.112	90/50					371.197	250/250	
366.115	90/56					372.185	315/110	
366.125	90/75					372.189	315/125	
366.130	90/90					372.195	315/160	
367.112	110/50					372.196	315/200	
367.115	110/56					372.197	315/250	
367.120	110/63					372.198	315/315	
367.125	110/75							
367.130	110/90							
				Reduktion, lang, exzentrisch				
			368.584	125/110				
			369.584	160/110				
			369.587	160/125				
			370.584	200/110				
			370.587	200/125				
			370.594	200/160				
			371.596	250/200				
			372.596	315/200				
			372.598	315/250				

weitere Dimensionen siehe nächste Spalte ==>

Art.-Nr.	Dimension	Anzahl	Art.-Nr.	Dimension	Anzahl	Art.-Nr.	Dimension	Anzahl
	PE-Bogenabzweiger 88 1/2°			Elektroschweißmuffe			Langmuffe mit Dichtung für waagrechte und senkrechte Montage	
367.163	110/110		360.771	40		369.700	160	
			361.771	50		370.700	200	
			363.771	56		371.700	250	
			364.771	63		372.700	315	
			365.771	75				
			366.771	90				
			367.771	110				
			368.771	125				
			369.771	160				
	Reduktion, zentrisch						Verschraubung, komplett	
360.557	40/32					379.740	32	
361.557	50/32					360.740	40	
						361.740	50	
						363.740	56	
						364.740	63	
						365.740	75	
						366.740	90	
						367.740	110	
	Reduktion, exzentrisch			Thermoschweißmuffe				
361.558	50/40		370.775	200				
363.558	56/40		371.775	250				
363.561	56/50		372.775	315				
364.558	63/40							
364.561	63/50							
364.566	63/56							
365.558	75/40							
365.561	75/50							
365.566	75/56							
365.571	75/63							
366.561	90/50							
366.566	90/56							
366.571	90/63							
366.576	90/75							
367.558	110/40							
367.561	110/50							
367.566	110/56							
367.571	110/63							
367.576	110/75							
367.581	110/90							
368.561	125/50							
368.566	125/56							
368.571	125/63							
368.576	125/75							
368.581	125/90							
368.586	125/110							
369.586	160/110							
369.588	160/125							
369.591	160/140							
				Steckmuffe mit Dichtung			Bundbüchse	
			360.779	40		379.772	32	
			361.779	50		360.772	40	
			363.779	56		361.772	50	
			364.779	63		363.772	56	
			365.779	75		364.772	63	
			366.779	90		365.772	75	
			367.779	110		366.772	90	
			368.779	125		367.772	110	
			369.779	160				
				Hosen-T, 60°			Verschlusskappe komplett	
			364.462	63		379.750	32	
			365.470	75		360.750	40	
						361.750	50	
						363.750	56	
						364.750	63	
						365.750	75	
						366.750	90	
						367.750	110	
				Langmuffe mit Dichtung für waagrechte und senkrechte Montage				
			379.791	32				
			360.700	40				
			361.700	50				
			363.700	56				
			364.700	63				
			365.700	75				
			366.700	90				
			367.700	110				
			368.700	125				
							PE-Wand-WC-Bogen 90° für senkrechte Montage	
						366.925	90/90	
						367.925	110/90	
						367.792	110/110	

weitere Dimensionen siehe nächste Spalte
=>

Art.-Nr.	Dimension	Anzahl	Art.-Nr.	Dimension	Anzahl	Art.-Nr.	Dimension	Anzahl
	PE-Wand-WC-Bogen 90°, rechts für waagrechte Montage			Siphonanschlusswinkel			PE-Anschweißende mit Außengewinde	
366.913	90/90		360.061	40/46		361.726	50/1 1/4"	
367.913	110/90		361.065	50/58		361.727	50/1 1/2"	
367.901	110/110		363.065	56/58		363.728	56/2"	
						364.728	63/2"	
						365.729	75/2 1/2"	
	PE-Wand-WC-Bogen 90°, links für waagrechte Montage			Steckdichtungen zu Siphonanschlusswinkel			PE-Anschweißenden mit Innengewinde	
366.914	90/90		152.495	46x32 mm		360.719	40/1/2"	
367.914	110/90		152.496	46x40 mm		360.720	40/3/4"	
367.902	110/110		153.564	58x32 mm		360.721	40/1"	
			153.565	58x40 mm		361.719	50/1/2"	
			153.566	58x50 mm		361.720	50/3/4"	
	PE-Wand-WC-Doppelbogen 90° für senkrechte Montage			Übergang Geberit/Guß muffenlos		361.721	50/1"	
367.923	110/90		359.268	125/135		361.722	50/1 1/4"	
367.903	110/110		370.738	200/212		361.723	50/1 1/2"	
			371.738	250/274		363.724	56/2"	
			372.738	315/326		364.724	63/2"	
	PE-Wand-WC-Doppelbogen 90° für waagrechte Montage			Bride Geberit/Guß muffenlos DN 70			Brandschutzmanschette RS90Plus EN	
367.485	110/90		359.434	75-76		348.300	40-56	
367.904	110/110					348.301	63-75	
						348.302	90	
	Siphonanschlussbogen			Chromstahl Stützring , als Verstärkung zum Einschlagen ins PE-Rohrende		348.303	110	
361.080	50/50		359.455	56		348.304	125/135	
363.083	56/50		359.456	63		348.305	160	
363.080	56/56		359.457	75		348.306	200	
364.084	56/63		359.458	90				
			359.459	110			Rohrbelüftungsventil	
	Doppelpbogen 2x90°		359.464	160		359.900	32-63	
361.498	50/50							
	Steckdichtungen zu Siphonanschlussbogen u. Doppelbogen						Rohrbelüftungsventil	
152.682	44/32					310.006	PE 75-110	
152.796	44/40							
152.689	50/32							
152.690	50/40							
152.691	57/32							
152.692	57/40							
152.693	57/50							